



## ПВБШВ 3x185-1 ГОСТ 16442-80, ТУ У 31.3-00214534-048:2007

Power cables with copper conductors, XLPE-insulated, galvanized steel-tape armoured, with PVC-compound protection hose

Cables are used for laying:

- *single laying*
- *in premises, dry ducts and tunnels, in corrosive environment*
- *in places, where small mechanical impacts on cable are possible, including tensile forces*

Manufacturing of non-galvanized armoured cable, covered with a layer of bitumen and PET film is possible  
 Manufacturing of cable with PVC compound belt insulation is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

### TECHNICAL SPECIFICATIONS

|                                                                          |                 |                                    |
|--------------------------------------------------------------------------|-----------------|------------------------------------|
| Rated voltage                                                            | kV              | 1                                  |
| Number and rated area of conductors                                      | mm <sup>2</sup> | 3 x 185                            |
| Phase insulation thickness                                               | mm              | 1.6                                |
| Permissible continuous current rating (AC of industrial frequency) *     |                 |                                    |
| • <i>by aerial laying</i>                                                | A               | 504                                |
| • <i>by burial</i>                                                       | A               | 442                                |
| Maximum permissible conductor temperature                                |                 |                                    |
| • <i>Continuous</i>                                                      | °C              | +90                                |
| • <i>in emergency operation</i>                                          | °C              | +130                               |
| • <i>at short circuit</i>                                                | °C              | +250                               |
| Operating temperature range                                              | °C              | -50 ... +50                        |
| Minimum bending radius by laying                                         | mm              | 367.5                              |
| Rated outer diameter of the cable (for reference) **                     | mm              | 49                                 |
| Cable weight (approximate)                                               | kg/km           | 6410                               |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 18: 460 • 3.4<br># 20: 740 • 5.4 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



**ПвБ6Шв 3x185-1**  
**ГОСТ 16442-80, ТУ У 31.3-00214534-048:2007**

Power cables with copper conductors, XLPE-insulated, galvanized steel-tape armoured, with PVC-compound protection hose



### CONSTRUCTION

1. Copper multiwire compact conductor
  2. XLPE insulation
  3. Tape core wrapping
  4. Double galvanized steel-tape armour
  5. Pressed PVC compound protection hose
- Note: conductor twisting is not illustrated*