

## СИП-4 4x35+1x35 ТУ У 31.3-00214534-014-2002

Self-supporting wires with light-stabilized thermoplastic polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage of 0.6/1 kV*
- *branches to the inputs into dwellings and outbuildings*

### TECHNICAL SPECIFICATIONS


|                                                                          |                 |                                                           |
|--------------------------------------------------------------------------|-----------------|-----------------------------------------------------------|
| Rated voltage                                                            | kV              | 0.6 / 1                                                   |
| Number and rated area of phase conductors                                | mm <sup>2</sup> | 4 x 35                                                    |
| Number and rated area of additional conductors for light circuits        | mm <sup>2</sup> | 1 x 35                                                    |
| Phase insulation thickness                                               | mm              | 1.6                                                       |
| Current ratings *                                                        |                 |                                                           |
| • <i>Continuous</i>                                                      | A               | 115                                                       |
| • <i>at short circuit (not more than 1 s)</i>                            | kA              | 2.3                                                       |
| Maximum permissible conductor temperature                                |                 |                                                           |
| • <i>Continuous</i>                                                      | °C              | +70                                                       |
| • <i>at short circuit (not more than 5 s)</i>                            | °C              | +135                                                      |
| Operating temperature range                                              | °C              | -60 ... +50                                               |
| Permissible temperature of laying (installation), no less than           | °C              | -20                                                       |
| Minimum bending radius by laying                                         | mm              | 273                                                       |
| Rated outer diameter of the cable (for reference) **                     | mm              | 27.3                                                      |
| Weight (approximate)                                                     | kg/km           | 680                                                       |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 1290 • 1.1<br># 18: 1480 • 1.5<br># 20: 2360 • 2.2 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



## СИП-4 4x35+1x35 ТУ У 31.3-00214534-014-2002

Self-supporting wires with light-stabilized thermoplastic polyethylene insulation

### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Multiwire compacted aluminium assisting conductor for light circuits
3. Light-stabilized thermoplastic polyethylene insulation

Note: wire lay-up is not illustrated

