

## СИП-4 4x70 ТУ У 31.3-00214534-014-2002

Self-supporting wires with light-stabilized thermoplastic polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage of 0.6/1 kV*
- *branches to the inputs into dwellings and outbuildings*

### TECHNICAL SPECIFICATIONS


|                                                                          |                 |                                                          |
|--------------------------------------------------------------------------|-----------------|----------------------------------------------------------|
| Rated voltage                                                            | kV              | 0.6 / 1                                                  |
| Number and rated area of phase conductors                                | mm <sup>2</sup> | 4 x 70                                                   |
| Phase insulation thickness                                               | mm              | 1.8                                                      |
| Current ratings *                                                        |                 |                                                          |
| • <i>Continuous</i>                                                      | A               | 180                                                      |
| • <i>at short circuit (not more than 1 s)</i>                            | kA              | 4.5                                                      |
| Maximum permissible conductor temperature                                |                 |                                                          |
| • <i>Continuous</i>                                                      | °C              | +70                                                      |
| • <i>at short circuit (not more than 5 s)</i>                            | °C              | +135                                                     |
| Operating temperature range                                              | °C              | -60 ... +50                                              |
| Permissible temperature of laying (installation), no less than           | °C              | -20                                                      |
| Minimum bending radius by laying                                         | mm              | 319                                                      |
| Rated outer diameter of the cable (for reference) **                     | mm              | 31.9                                                     |
| Weight (approximate)                                                     | kg/km           | 980                                                      |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 990 • 1.2<br># 18: 1130 • 1.6<br># 20: 1810 • 2.4 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## СИП-4 4x70 ТУ У 31.3-00214534-014-2002

Self-supporting wires with light-stabilized thermoplastic polyethylene insulation

### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Light-stabilized thermoplastic polyethylene insulation

Note: wire lay-up is not illustrated

