



## СИП-2 3x25+1x54.6+1x25 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation, with neutral carrier insulated conductor

Used for laying:

- *trunks of aerial electric power lines and line branches for the rated voltage of 0.6/1 kV*
- *in air, types II and III according to ГОСТ 15150-69, including on sea coasts, salt lakes, in industrial areas and areas of saline sands*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

### TECHNICAL SPECIFICATIONS

|                                                                          |                 |                   |
|--------------------------------------------------------------------------|-----------------|-------------------|
| Rated voltage                                                            | kV              | 0.6 / 1           |
| Number and rated area of phase conductors                                | mm <sup>2</sup> | 3 x 25            |
| Number and rated area of additional conductors for light circuits        | mm <sup>2</sup> | 1 x 25            |
| Carrier neutral conductor rated area                                     | mm <sup>2</sup> | 54.6              |
| Phase insulation thickness                                               | mm              | 1.3               |
| Current ratings *                                                        |                 |                   |
| • <i>Continuous</i>                                                      | A               | 130               |
| • <i>at short circuit (not more than 1 s)</i>                            | kA              | 2.3               |
| Maximum permissible conductor temperature                                |                 |                   |
| • <i>Continuous</i>                                                      | °C              | +90               |
| • <i>at short circuit (not more than 5 s)</i>                            | °C              | +250              |
| Operating temperature range                                              | °C              | -60 ... +50       |
| Permissible temperature of laying (installation), no less than           | °C              | -20               |
| Minimum bending radius by laying                                         | mm              | 293               |
| Rated outer diameter of the cable (for reference) **                     | mm              | 29.3              |
| Weight (approximate)                                                     | kg/km           | 590               |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 1120 • 0.9 |
|                                                                          |                 | # 18: 1290 • 1.2  |
|                                                                          |                 | # 20: 2060 • 1.9  |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



## СИП-2 3x25+1x54.6+1x25 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation, with neutral carrier insulated conductor

### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Multiwire aluminium-alloy compacted supporting conductor
3. Multiwire compacted aluminium assisting conductor for light circuits
4. Light-stabilized cross-linked polyethylene insulation

*Note: wire lay-up is not illustrated*

