



## СИП-4 4x50 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage of 0.6/1 kV*
- *branches from aerial electric power lines for the rated voltage of 0.6/1 kV to the input and for the laying on the walls of buildings and engineering structures*
- *in air, types II and III according to ГОСТ 15150-69*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

### TECHNICAL SPECIFICATIONS

|                                                                          |                 |                                                           |
|--------------------------------------------------------------------------|-----------------|-----------------------------------------------------------|
| Rated voltage                                                            | kV              | 0.6 / 1                                                   |
| Number and rated area of phase conductors                                | mm <sup>2</sup> | 4 x 50                                                    |
| Phase insulation thickness                                               | mm              | 1.5                                                       |
| Current ratings *                                                        |                 |                                                           |
| • <i>Continuous</i>                                                      | A               | 195                                                       |
| • <i>at short circuit (not more than 1 s)</i>                            | kA              | 4.6                                                       |
| Maximum permissible conductor temperature                                |                 |                                                           |
| • <i>Continuous</i>                                                      | °C              | +70                                                       |
| • <i>at short circuit (not more than 5 s)</i>                            | °C              | +135                                                      |
| Operating temperature range                                              | °C              | -60 ... +50                                               |
| Permissible temperature of laying (installation), no less than           | °C              | -20                                                       |
| Minimum bending radius by laying                                         | mm              | 265                                                       |
| Rated outer diameter of the cable (for reference) **                     | mm              | 26.5                                                      |
| Weight (approximate)                                                     | kg/km           | 690                                                       |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 1500 • 1.3<br># 18: 1710 • 1.6<br># 20: 2740 • 2.5 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



## СИП-4 4x50 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Light-stabilized cross-linked polyethylene insulation

*Note: wire lay-up is not illustrated*

