



## **КВВГнгд 14х0.75** **ТУ У 31.3-00214534-018-2003**

Control flame-retardant cables with copper conductors, low fire-risk PVC compound insulation, PVC compound sheath, low smoke and gas emission

Cables are used for laying:

- *in premises, dry ducts and tunnels, in corrosive environment*
- *with no risk of mechanical damage in operation*
- *in bunches, in crowded places*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ123121000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*
- *toxicity class Tk3 of the combustion products of nonmetallic elements (toxicity index over 120 g/m<sup>3</sup>)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m<sup>2</sup>/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Кк1 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH less than 4.3, specific conductivity more than 10 μS/mm)*

### **TECHNICAL SPECIFICATIONS**

|                                                                          |                 |                  |
|--------------------------------------------------------------------------|-----------------|------------------|
| Rated voltage (AC / DC)                                                  | V               | 660 / 1000       |
| Number and rated area of conductors                                      | mm <sup>2</sup> | 14 x 0.75        |
| Minimum bending radius by laying                                         | mm              | 78               |
| Cable outer diameter (for reference only) **                             | mm              | 13               |
| Cable weight (approximate)                                               | kg/km           | 250              |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 10: 1410 • 0.4 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## КВВГнгд 14х0.75 ТУ У 31.3-00214534-018-2003

Control flame-retardant cables with copper conductors, low fire-risk PVC compound insulation, PVC compound sheath, low smoke and gas emission

### CONSTRUCTION

1. Copper conductor
2. Low fire-risk PVC compound insulation
3. PET film winding
4. Low fire-risk PVC compound outer sheath

*Note: conductor twisting is not illustrated*

