



## СБПл 7х0.9 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, with water-blocking core filling, in thickened polyethylene sheath

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- in soil (trenches), in corrosion environment
- in conditions of excessive humidity
- in the absence of mechanical effects on cable

### TECHNICAL SPECIFICATIONS

|                                                                          |        |                  |
|--------------------------------------------------------------------------|--------|------------------|
| Rated voltage                                                            | V      | 380 / 700        |
| Number and rated diameter of conductors                                  | mm     | 7 x 0.9          |
| Electrical resistance of the conductor at 20 °C                          | Ohm/km | 23.3             |
| Operating capacity, not more than                                        | nF/km  | 150.0            |
| Operating temperature range                                              | °C     | -50 ... +60      |
| Minimum bending radius by laying                                         | mm     | 84               |
| Cable outer diameter (for reference only) **                             | mm     | 12               |
| Cable weight (approximate)                                               | kg/km  | 134              |
| Rated factory cable length and gross weight of the delivery on the drums | m, t   | # 10: 1650 • 0.3 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\*\* The external diameter may differ from the rated up to  $\pm 10\%$

### CONSTRUCTION

1. Copper conductor
2. Polyethylene insulation
3. Water-blocking filling
4. Polyethylene inner sheath
5. Polyethylene outer sheath

Note: conductor twisting is not illustrated

