

## **АПвЕАкПнг-6 1х35** **ТУ У 31.3-00214534-017-2003**

Single-core power cables with aluminium conductor, flame-retardant, with XLPE, aluminium-wire armoured, with polymer compound outer sheath

Due to non-magnetic armour, cables operate at AC  
Technical cable requirements correspond to IEC 60502-2

Cables are used for laying:

- *in places, where small mechanical impacts on cable are possible, including tensile forces*
- *in premises, tunnels, ducts, mines, dry soil and outdoor under shelter*
- *single laying*

It is possible to manufacture cables with extruded semiconductor layer along outer sheath.

Order entry example:

АПвЕАкПнг-П-6 1х35/16 ТУ У 31.3-00214534-017-2003

An extruded semiconductor layer along outer sheath ensures the correct testing of cable line with sections of underground laying in polymer pipes.

It is possible to manufacture cables with an integrated fiber-optic module.

Order entry example:

АПвЕАкПнг-6 1х35/16 (ОМ) ТУ У 31.3-00214534-017-2003

In conjunction with the DTS system, the integrated fiber-optic module can act as a distributed cable line temperature sensor.

It is possible to manufacture cable with

Order entry example:

АПвЕАкПнг-6 1х35/16 (ожк) ТУ У 31.3-00214534-017-2003

It is possible to manufacture cable with sealed conductor.

Order entry example:

АПвЕАкПнг-6 1х35/16 (г) ТУ У 31.3-00214534-017-2003

It is possible manufacturing of cables in versions (A) and (B), flame-retardant when laying in bunches

It is possible to supply of three stranded single-core cables.


Order entry example:

3хАПвЕАкПнг-6 1х35/16 ТУ У 31.3-00214534-017-2003

Fire safety code in accordance with ДСТУ 4809:2007: ПБ101122000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *toxicity class Tk1 of the combustion products of nonmetallic elements (toxicity index from 13 up to 40 g/m<sup>3</sup>)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m<sup>2</sup>/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Кк2 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH more than 4.3, specific conductivity less than 10 μS/mm)*



## АПвЕАкПнг-6 1x35 ТУ У 31.3-00214534-017-2003

Single-core power cables with aluminium conductor, flame-retardant, with XLPE, aluminium-wire armoured, with polymer compound outer sheath

### TECHNICAL SPECIFICATIONS

|                                                                              |                 |                                                 |
|------------------------------------------------------------------------------|-----------------|-------------------------------------------------|
| Rated voltage                                                                | kV              | 6                                               |
| Maximum voltage                                                              | kV              | 7.2                                             |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 1 x 35                                          |
| Insulation thickness                                                         | mm              | 2.5                                             |
| Minimum screen cross-section                                                 | mm <sup>2</sup> | 16                                              |
| Permissible short circuit current across the screen of minimum cross-section | kA              | 3.3                                             |
| Maximum permissible short-circuit current in core                            | kA              | 3.3                                             |
| Permissible continuous current rating *                                      |                 |                                                 |
| • by aerial laying in trefoil formation                                      | A               | 154                                             |
| • by aerial flat laying                                                      | A               | 185                                             |
| • by burial in trefoil formation                                             | A               | 129                                             |
| • by burial flat                                                             | A               | 134                                             |
| Partial discharge factor for rated voltage, not more than                    | pC              | 6                                               |
| Maximum permissible conductor temperature                                    |                 |                                                 |
| • Continuous                                                                 | °C              | +90                                             |
| • in emergency operation                                                     | °C              | +130                                            |
| • at short circuit                                                           | °C              | +250                                            |
| Operating temperature range                                                  | °C              | -60 ... +50                                     |
| Minimum bending radius by laying                                             | mm              | 512                                             |
| Rated outer diameter of the cable (for reference) **                         | mm              | 32                                              |
| Cable weight (approximate)                                                   | kg/km           | 1240                                            |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 18УД-40: 1035 • 1.8<br># 18аУД-40: 1597 • 2.5 |


#### Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: conductor temperature 90 °C, air temperature 30 °C, soil temperature 20 °C, thermal resistivity of soil 1.5 °K·m/W, laying depth in the soil 0.8 m, while laying in flat formation the distance between cables in clear is equal to the cable diameter, while laying in trefoil formation cables are laid side by side, shields are earthed on both ends of the line


\*\* The external diameter may differ from the rated up to ± 10 %

\*\*\* Отклонение фактической массы брутто от указанного значения может составлять ± 7 %



## АПвЕАкПнг-6 1х35 ТУ У 31.3-00214534-017-2003

Single-core power cables with aluminium conductor, flame-retardant, with XLPE, aluminium-wire armoured, with polymer compound outer sheath



### CONSTRUCTION

#### 1. Aluminium multiwire compacted conductor

*Note: It is possible to manufacture cable with sealed conductor.*

#### 2. Inner extruded semiconducting layer

#### 3. XLPE insulation

#### 4. Outer extruded semiconducting layer

#### 5. Lapping layer of semiconductive swellable tape

#### 6. Copper screen

#### 7. Lapping layer of nonwoven cloth tape

#### 8. Extruded bedding of polyethylene

#### 9. Aluminium-wire armour

#### 10. Flame-retardant polymer compound outer sheath

*Note: It is possible to manufacture cable with extruded semiconductor layer along outer sheath*