



**ПвЕВ-30 3x120**  
**TY Y 31.3-00214534-017-2003**

Power cables with copper conductors, with XLPE and with PVC compound outer sheath

---

For the cable of this mark correspond the foreign-made analogues:

N2XSEY (DE) • 2XSEY (DE) • Cu/XLPE/CWS/PVC (GB) • ПвВ (RU)

Technical cable requirements correspond to IEC 60502-2

---

Cables are used for laying:

- *in premises, tunnels, ducts, mines, dry soil and outdoor under shelter*
  - *single laying*
- 

It is possible to manufacture cables with an integrated fiber-optic module.

Order entry example:

ПвЕВ-30 3x120/16 (OM) TY Y 31.3-00214534-017-2003

In conjunction with the DTS system, the integrated fiber-optic module can act as a distributed cable line temperature sensor.

---

It is possible to manufacture cable with sealed conductors.

Order entry example:

ПвЕВ-30 3x120/16 (r) TY Y 31.3-00214534-017-2003

---

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*



## ПвББ-30 3x120 TY Y 31.3-00214534-017-2003

Power cables with copper conductors, with XLPE and with PVC compound outer sheath

### TECHNICAL SPECIFICATIONS

|                                                                              |                 |                                               |
|------------------------------------------------------------------------------|-----------------|-----------------------------------------------|
| Rated voltage                                                                | kV              | 30                                            |
| Maximum voltage                                                              | kV              | 36                                            |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 120                                       |
| Insulation thickness                                                         | mm              | 8                                             |
| Minimum screen cross-section                                                 | mm <sup>2</sup> | 16                                            |
| Permissible short circuit current across the screen of minimum cross-section | kA              | 3.3                                           |
| Maximum permissible short-circuit current in core                            | kA              | 17.2                                          |
| Permissible continuous current rating *                                      |                 |                                               |
| • by aerial laying                                                           | A               | 351                                           |
| • by burial                                                                  | A               | 298                                           |
| Partial discharge factor for rated voltage, not more than                    | pC              | 6                                             |
| Maximum permissible conductor temperature                                    |                 |                                               |
| • Continuous                                                                 | °C              | +90                                           |
| • in emergency operation                                                     | °C              | +130                                          |
| • at short circuit                                                           | °C              | +250                                          |
| Operating temperature range (in climate version NF)                          | °C              | -50 ... +50                                   |
| Operating temperature range (in climate version T)                           | °C              | -25 ... +65                                   |
| Minimum bending radius by laying                                             | mm              | 1264                                          |
| Rated outer diameter of the cable (for reference) **                         | mm              | 79                                            |
| Cable weight (approximate)                                                   | kg/km           | 8720                                          |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 25УД-90: 443 • 5.4<br># 26УД-100: 631 • 7.3 |

#### Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: conductor temperature 90 °C, air temperature 30 °C, soil temperature 20 °C, load factor 1.0, thermal resistivity of soil 1.5 °K • m/W, laying depth in the ground 0.8 m, shields are grounded at both ends of the line


\*\* The external diameter may differ from the rated up to ± 10 %

\*\*\* Отклонение фактической массы брутто от указанного значения может составлять ± 7 %



## ПвБВ-30 3x120 ТУ У 31.3-00214534-017-2003

Power cables with copper conductors, with XLPE and with PVC compound outer sheath



### CONSTRUCTION

#### 1. Copper multiwire compact conductor

*Note: It is possible to manufacture cable with sealed conductors.*

#### 2. Inner extruded semiconducting layer

#### 3. XLPE insulation

#### 4. Outer extruded semiconducting layer

#### 5. Lapping layer of semiconductive swellable tape

#### 6. Copper screen

#### 7. PVC compound outer sheath

*Note: Conductor twisting is not illustrated*