**ААБлГ 4х95(ож)-1**  
**ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, aluminium-sheathed, steel-tape armoured

Cables are used for laying:

- *in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness*
- *in fire-risk premises*
- *on technological trestles*
- *on special cable bridges*
- *on bridges*
- *with a risk of mechanical damage and no tensile forces in operation*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

**TECHNICAL SPECIFICATIONS**


|                                                                              |                 |                  |
|------------------------------------------------------------------------------|-----------------|------------------|
| Rated voltage                                                                | kV              | 1                |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 4 x 95           |
| Insulation thickness between conductors                                      | mm              | 1.5              |
| Insulation thickness of conductor-sheath                                     | mm              | 1.25             |
| Sheath thickness                                                             | mm              | 1.4              |
| Permissible continuous current rating *                                      |                 |                  |
| • <i>by aerial laying</i>                                                    | A               | 203              |
| • <i>by burial</i>                                                           | A               | 204              |
| Operating temperature range                                                  | °C              | -50 ... +50      |
| Minimum bending radius by laying                                             | mm              | 950              |
| Level difference along the laying route, not more than                       | m               | 25               |
| Metal sheath outer diameter (for reference only)                             | mm              | 31               |
| Rated outer diameter of the cable (for reference) **                         | mm              | 38               |
| Cable weight (approximate)                                                   | kg/km           | 2550             |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16a: 700 • 2.0 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*


*\* Long permissible current loads are calculated during operation in four-wire networks with load in all the conductors for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## ААБлГ 4х95(ож)-1 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, aluminium-sheathed, steel-tape armoured



### CONSTRUCTION

1. Aluminium conductor
2. Impregnated paper insulation
3. Belt insulation
4. Aluminium sheath
5. Single-layer plastic-tape bedding
6. Double galvanized steel-tape armour

*Note: Conductor twisting is not illustrated*