

**АСПл 4x150-1**  
**ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-wire armoured

Cables are used for laying:

- *in soil (trenches) with medium corrosiveness, as well as with vagabond currents*
- *with a risk of mechanical damage and tensile forces in operation*

**TECHNICAL SPECIFICATIONS**

|                                                                              |                 |                                    |
|------------------------------------------------------------------------------|-----------------|------------------------------------|
| Rated voltage                                                                | kV              | 1                                  |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 4 x 150                            |
| Insulation thickness between conductors                                      | mm              | 1.7                                |
| Insulation thickness of conductor-sheath                                     | mm              | 1.45                               |
| Sheath thickness                                                             | mm              | 1.52                               |
| Permissible continuous current rating *                                      |                 |                                    |
| • <i>by aerial laying</i>                                                    | A               | 279                                |
| • <i>by burial</i>                                                           | A               | 261                                |
| Operating temperature range                                                  | °C              | -50 ... +50                        |
| Minimum bending radius by laying                                             | mm              | 840                                |
| Level difference along the laying rout, not more than                        | m               | 25                                 |
| Metal sheath outer diameter (for reference only)                             | mm              | 40                                 |
| Rated outer diameter of the cable (for reference) **                         | mm              | 56                                 |
| Cable weight (approximate)                                                   | kg/km           | 7390                               |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 18: 370 • 3.2<br># 20: 590 • 5.0 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\* Long permissible current loads are calculated during operation in four-wire networks with load in all the conductors for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## АСПл 4х150-1 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-wire armoured

### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Lead sheath
6. Single-layer plastic-tape bedding
7. Round galvanized steel-wire armour
8. Outer covering

*Note: Conductor twisting is not illustrated*

