

## АСП2л 3х240-6 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-wire armoured

Cables are used for laying:

- *in soil (trenches) with high corrosiveness, as well as with vagabond currents*
- *with a risk of mechanical damage and tensile forces in operation*

### TECHNICAL SPECIFICATIONS


|                                                                              |                 |                                    |
|------------------------------------------------------------------------------|-----------------|------------------------------------|
| Rated voltage                                                                | kV              | 6                                  |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 240                            |
| Insulation thickness between conductors                                      | mm              | 4                                  |
| Insulation thickness of conductor-sheath                                     | mm              | 2.95                               |
| Sheath thickness                                                             | mm              | 1.66                               |
| Permissible continuous current rating *                                      |                 |                                    |
| • <i>by aerial laying</i>                                                    | A               | 389                                |
| • <i>by burial</i>                                                           | A               | 351                                |
| Operating temperature range                                                  | °C              | -50 ... +50                        |
| Minimum bending radius by laying                                             | mm              | 960                                |
| Level difference along the laying rout, not more than                        | m               | 15                                 |
| Metal sheath outer diameter (for reference only)                             | mm              | 48                                 |
| Rated outer diameter of the cable (for reference) **                         | mm              | 64                                 |
| Cable weight (approximate)                                                   | kg/km           | 9290                               |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 18: 270 • 3.0<br># 20: 440 • 4.7 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*


*\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## АСП2л 3x240-6 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-wire armoured



### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath
7. Double-layer plastic-tape bedding
8. Round galvanized steel-wire armour
9. Outer covering

Note: Conductor twisting is not illustrated