



## **ПВБГ 3x6+1x4-1** **TY Y 31.3-00214534-048:2007**

Power cables with copper conductors, XLPE-insulated, with PVC-compound outer sheath

Cables are used for laying:

- *single laying*
- *in premises, dry ducts and tunnels, in corrosive environment*

Manufacturing of cable with PVC compound belt insulation is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ1000000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

### **TECHNICAL SPECIFICATIONS**

|                                                                              |                 |                                      |
|------------------------------------------------------------------------------|-----------------|--------------------------------------|
| Rated voltage                                                                | kV              | 1                                    |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 6 + 1 x 4                        |
| Phase insulation thickness                                                   | mm              | 0.7                                  |
| Permissible continious current rating (AC of industrial frequency) *         |                 |                                      |
| • <i>by aerial laying</i>                                                    | A               | 56                                   |
| • <i>by burial</i>                                                           | A               | 64                                   |
| Maximum permissible conductor temperature                                    |                 |                                      |
| • <i>Continuous</i>                                                          | °C              | +90                                  |
| • <i>in emergency operation</i>                                              | °C              | +130                                 |
| • <i>at short circuit</i>                                                    | °C              | +250                                 |
| Operating temperature range                                                  | °C              | -50 ... +50                          |
| Minimum bending radius by laying                                             | mm              | 105                                  |
| Rated outer diameter of the cable (for reference) **                         | mm              | 14                                   |
| Cable weight (approximate)                                                   | kg/km           | 300                                  |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 10: 1210 • 0.4<br># 12: 1670 • 0.6 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



**ПВВГ 3x6+1x4-1**  
**ТУ У 31.3-00214534-048:2007**

Power cables with copper conductors, XLPE-insulated, with PVC-compound outer sheath



### CONSTRUCTION

1. Copper conductor
2. XLPE insulation
3. PET film winding
4. PVC compound outer sheath

*Note: Conductor twisting is not illustrated*