



КВП6ШВ 27x1.5 ТУ У 27.3-00214534-103:2018

Control cables with copper conductors, galvanized steel-wire armoured, with PVC compound insulation, PVC compound protection hose

Cables are used for laying:

- in premises, dry ducts and tunnels, in corrosive environment
- single laying
- in places, where intense tensile forces are possible (in cable lifting, in bulk, heaving, boggy, everfrost soils, in water)

Fire safety code in accordance with ДСТУ 4809:2007: ПБ1000000000

Products of this mark meet the requirements:

- single wire cable flame retardance

TECHNICAL SPECIFICATIONS

Rated voltage (AC / DC)	V	660 / 1000
Number and rated area of conductors	mm ²	27 x 1.5
Minimum bending radius by laying	mm	300
Cable outer diameter (for reference only) **	mm	30
Cable weight (approximate)	kg/km	2380
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 14: 700 • 1.9 # 16a: 1120 • 2.9

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

** The external diameter may differ from the rated up to $\pm 10\%$

CONSTRUCTION

1. Copper conductor
2. PVC compound insulation
3. PET film winding
4. PVC compound belt insulation
5. Round galvanized steel-wire armour
6. Pressed PVC compound protection hose

Note: Conductor twisting is not illustrated

