



NYM-J 5x1.5

DIN VDE 0250-204

Power cables with copper conductors, PVC compound insulation, outer PVC compound sheath

Cable technical specifications conform DIN VDE 0250 p.204

Cables are used for:

- *electric wiring and cable lines installation in industrial, residential and public buildings and facilities*
- *laying over the plaster, inside and under plaster, in brick masonry and concrete, in pipes and ducts*
- *outdoor installation, if protected from sun rays*

Manufacturing of cables with light-stabilized outer sheath is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ1000000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.66
Number and rated area of conductors	mm ²	5 x 1.5
Insulation thickness	mm	0.6
Permissible continious current rating *		
• <i>by aerial laying (AC of industrial frequency) *</i>	A	19
Operating temperature range	°C	-50 ... +50
Minimum bending radius by laying	mm	40
Rated outer diameter of the cable (for reference) **	mm	10
Cable weight (approximate)	kg/km	180

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

** Long permissible current loads are calculated for the air temperature plus 25 °C*

*** The external diameter may differ from the rated up to ± 10 %*



NYM-J 5x1.5 **DIN VDE 0250-204**

Power cables with copper conductors, PVC compound insulation, outer PVC compound sheath

CONSTRUCTION

1. *Copper conductor*
2. *PVC compound insulation*
3. *Extruded uncured stock inner sheath*
4. *PVC compound outer sheath*

Note: Manufacturing of cables with light-stabilized outer sheath is possible

Note: Conductor twisting is not illustrated

