

## **ПВ1нгд 1 x 95** **ТУ У 31.3-00214534-056:2006**

Installation wires with copper conductors, low fire-risk PVC compound insulation

Used for:

- *fixed laying in lighting and power circuits and also for electric equipment, machines, mechanisms and machine tools installation for rated voltage up to 450 V (for networks up to 450/750), frequency up to 100 Hz or constant voltage of 1000 V*
- *for laying in steel pipes, hollow ducts of building structures, on trays, etc.*

Manufacturing of wires in climate version F and T is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ142121000

Products of this mark meet the requirements:


- *single wire cable flame retardance*
- *bunched cable flame retardance category C*
- *toxicity class Tk2 of the combustion products of nonmetallic elements (toxicity index from 40 up to 120 g/m<sup>3</sup>)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m<sup>2</sup>/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Кк1 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH less than 4.3, specific conductivity more than 10 μS/mm)*

### **TECHNICAL SPECIFICATIONS**

|                                                                              |                 |                  |
|------------------------------------------------------------------------------|-----------------|------------------|
| Rated voltage                                                                | kV              | 0.45             |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 1 x 95           |
| Insulation thickness                                                         | mm              | 1.6              |
| Operating temperature range                                                  | °C              | -40 ... +50      |
| Flexibility class acc. to ГОСТ 22483-77                                      |                 | 2                |
| Minimum bending radius by laying                                             | mm              | 147              |
| Outer diameter (nominal, for reference only)                                 | mm              | 14.7             |
| Outer diameter (maximum, for reference only)                                 | mm              | 17               |
| Weight (approximate)                                                         | kg/km           | 940              |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 10: 1210 • 1.2 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*



**ПВ1нгд 1 x 95**  
**ТУ У 31.3-00214534-056:2006**

Installation wires with copper conductors, low fire-risk PVC compound insulation

**CONSTRUCTION**

1. *Copper multiwire conductor*
2. *Low fire-risk PVC compound insulation*

