
**МКЕШв 3x1  
ТУ У 27.3-00214534-119:2020**

## Multicore plastic-insulated wiring cables

Used:

- for industrial signal transmission lines for control, monitoring, signaling, regulation of electronic equipment and devices
- for industrial data transmission networks
- for inter-device installation of electrical installations

Cables are resistant to vibration and impact loads, to relative humidity of air up to 98% at temperatures up to 35 °C

It is possible to manufacture cables with a different number and nominal cross-section of wires, pair twisted cables, as well as fire-safe and halogen-free cables according to specifications of PJSC YUZH CABLE WORKS

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

**TECHNICAL SPECIFICATIONS**

Rated AC voltage up to 400 Hz	V	500
Rated DC voltage	V	750
Number and rated diameter of conductors	mm <sup>2</sup>	3 x 1
Class of core flexibility		2
Ambient operating temperature	°C	-50 ... +50
Permissible continuous conductors temperature	°C	+70
Cable outer diameter (for reference only) **	mm	8.4
Cable weight (approximate)	kg/km	118.5
Minimal service life	years	15


Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\*\* The external diameter may differ from the rated up to ± 10 %



454601-003010000100

**МКЕШв 3x1  
ТУ У 27.3-00214534-119:2020**

Multicore plastic-insulated wiring cables

**CONSTRUCTION**

1. *Tin coated copper multiwire current-carrying conductor*
2. *PVC compound insulation*
3. *Wrapping the core with polyethylene terephthalate film*
4. *Screen - copper wires braid*
5. *PVC compound outer sheath*