



## ААШп 3х240(ож)-10 TY Y 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, aluminium-sheathed, with polyethylene protection hose

Cables are used for laying:

- *in soil (trenches) with high corrosiveness, as well as with vagabond currents*
- *with no risk of mechanical damage in operation*

### TECHNICAL SPECIFICATIONS


|  |                 |                                    |
|--|-----------------|------------------------------------|
| Rated voltage  | kV              | 10                                 |
| Number and rated area of conductors  | mm <sup>2</sup> | 3 x 240                            |
| Insulation thickness between conductors                                      | mm              | 5.5                                |
| Insulation thickness of conductor-sheath                                     | mm              | 4                                  |
| Sheath thickness   | mm              | 1.8                                |
| Permissible continuous current rating *                                      |                 |                                    |
| • <i>by aerial laying</i>  | A               | 347                                |
| • <i>by burial</i>   | A               | 314                                |
| Operating temperature range  | °C              | -50 ... +50                        |
| Minimum bending radius by laying   | mm              | 1350                               |
| Level difference along the laying rout, not more than                        | m               | 15                                 |
| Metal sheath outer diameter (for reference only)                             | mm              | 48                                 |
| Rated outer diameter of the cable (for reference) **                         | mm              | 54                                 |
| Cable weight (approximate)   | kg/km           | 4190                               |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 20: 630 • 3.3<br># 22: 720 • 3.8 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## ААШп 3х240(ож)-10 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, aluminium-sheathed, with polyethylene protection hose



### CONSTRUCTION

1. Aluminium conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Aluminium sheath
7. Pressed off polyethylene protection hose

*Note: Conductor twisting is not illustrated*