

**АСБ2лШв 1х300-3**  
**ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured, with PVC-compound protection hose

Cables are used for laying:

- *in soil (trenches) with high corrosiveness, as well as with vagabond currents*
- *in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness*
- *with a risk of mechanical damage and no tensile forces in operation*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

**TECHNICAL SPECIFICATIONS**

|                                                                              |                 |                 |
|------------------------------------------------------------------------------|-----------------|-----------------|
| Rated voltage                                                                | kV              | 3               |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 1 x 300         |
| Insulation thickness of conductor-sheath                                     | mm              | 2.3             |
| Sheath thickness                                                             | mm              | 1.26            |
| Permissible continuous direct current rating *                               |                 |                 |
| • <i>by aerial laying</i>                                                    | A               | 695             |
| • <i>by burial</i>                                                           | A               | 562             |
| Operating temperature range                                                  | °C              | -50 ... +50     |
| Minimum bending radius by laying                                             | mm              | 1000            |
| Level difference along the laying route, not more than                       | m               | 25              |
| Metal sheath outer diameter (for reference only)                             | mm              | 28              |
| Rated outer diameter of the cable (for reference) **                         | mm              | 40              |
| Cable weight (approximate)                                                   | kg/km           | 3640            |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 18: 720 • 3.1 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## АСБ2лШв 1х300-3 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured, with PVC-compound protection hose



### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Lead sheath
4. Double-layer plastic-tape bedding
5. Double steel-tape armour
6. Pressed PVC compound protection hose