
**СИП-4 2x35**  
**ТУ У 31.3-00214534-014-2002**

Self-supporting wires with light-stabilized thermoplastic polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage of 0.6/1 kV*
- *branches to the inputs into dwellings and outbuildings*

**TECHNICAL SPECIFICATIONS**

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm <sup>2</sup>	2 x 35
Phase insulation thickness	mm	1.6
Current ratings *		
• <i>Continious</i>	A	115
• <i>at short circuit (not more than 1 s)</i>	kA	2.3
Maximum permissible conductor temperature		
• <i>Continious</i>	°C	+70
• <i>at short circuit (not more than 5 s)</i>	°C	+135
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	202
Rated outer diameter of the cable (for reference) **	mm	20.2
Weight (approximate)	kg/km	280
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 16a: 2530 • 1.0 # 18: 2890 • 1.3 # 20: 4630 • 1.9

Notes:


When ordering it is necessary to agree the factory length of the product with the manufacturer

 \* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>


\*\* The external diameter may differ from the rated up to ± 10 %



200105-012035000000

**СИП-4 2x35**  
**ТУ У 31.3-00214534-014-2002**

Self-supporting wires with light-stabilized thermoplastic polyethylene insulation

**CONSTRUCTION****1. Aluminium multiwire compacted conductor****2. Light-stabilized thermoplastic polyethylene insulation***Note: Wire lay-up is not illustrated.*