
СІП-4 4x120
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage of 0.6/1 kV*
- *branches from aerial electric power lines for the rated voltage of 0.6/1 kV to the input and for the laying on the walls of buildings and engineering structures*
- *in air, types II and III according to ГОСТ 15150-69*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

TECHNICAL SPECIFICATIONS

| | | |
|--|-----------------|---|
| Rated voltage | kV | 0.6 / 1 |
| Number and rated area of phase conductors | mm ² | 4 x 120 |
| Phase insulation thickness | mm | 1.7 |
| Current ratings * | | |
| • <i>Continious</i> | A | 340 |
| • <i>at short circuit (not more than 1 s)</i> | kA | 10.9 |
| Maximum permissible conductor temperature | | |
| • <i>Continious</i> | °C | +70 |
| • <i>at short circuit (not more than 5 s)</i> | °C | +135 |
| Operating temperature range | °C | -60 ... +50 |
| Permissible temperature of laying (installation), no less than | °C | -20 |
| Minimum bending radius by laying | mm | 390 |
| Rated outer diameter of the cable (for reference) ** | mm | 39 |
| Weight (approximate) | kg/km | 1570 |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t | # 16a: 630 • 1.2 # 18: 720 • 1.6 # 20: 1160 • 2.5 |

Notes:


When ordering it is necessary to agree the factory length of the product with the manufacturer

 * Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m²

** The external diameter may differ from the rated up to ± 10 %



200205-014120000000

**СІП-4 4x120**
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

CONSTRUCTION**1. Aluminium multiwire compacted conductor***Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials***2. Light-stabilized cross-linked polyethylene insulation***Note: Wire lay-up is not illustrated.*