**СБП 7x2x0.9**  
**ТУ У 31.3-00214534-008-2001**

Signal blocking cables with copper conductors, with polyethylene insulation, in thickened polyethylene sheath

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *in soil (trenches), in corrosion environment*
- *in the absence of mechanical effects on cable*

Manufacturing of cables with inner sheath of PVC-compound is possible


**TECHNICAL SPECIFICATIONS**

Rated voltage	V	380 / 700
Number of pairs and nominal conductor diameter		7 x 0.9
Electrical resistance of the conductor at 20 °C	Ohm/km	28.8
Operating capacity, not more than	nF/km	100.0
Attenuation coefficient of pairs at a temperature of 20 °C, not more than	dB/km	1.04
Coupling losses on near-end of cable between any pairs over a length of 300 m, not less than:		
• <i>for 100% of the values</i>	dB	60.0
• <i>for 80% of the values</i>	dB	62.0
Operating temperature range	°C	-50 ... +60
Minimum bending radius by laying	mm	112
Cable outer diameter (for reference only) **	mm	16
Cable weight (approximate)	kg/km	225
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 12: 1280 • 0.4

Notes:


*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## СБП 7х2х0.9 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, in thickened polyethylene sheath



### CONSTRUCTION

1. Copper conductor
2. Polyethylene insulation
3. PET film winding

4. Polyethylene inner sheath

*Note: Manufacturing of cables with inner sheath of PVC-compound is possible*

5. Polyethylene outer sheath

*Note: Pair twisting in the layer of core on the picture not shown.*