7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

500401-035060004072

ОБгПо * 6 – 3.5
ТУ У 31.3-00214534-050:2005

Fiber optic module-core cables, corrugated steel-tape armoured, with polyethylene outer sheath

Mark formation:
ОБгПо-[a]-[b] [c]6([d]x[e]+[f])-3.5
[a] central strength element
- *C – steel*
- *No marks – dielectric*

[b] quantity of optical fibers in the cable, possible values
- *4, 6, 8, 10, 12, 16, 18, 20, 22, 24, 28, 30, 32, 36, 40, 48, 60, 72, 78, 84, 90, 96*

[c] type of optical fiber
- *E – single-mode (ITU-T G.652B)*
- *A – single-mode with extended wavelength band (ITU-T G.652D, ITU-T G.657A1)*
- *C – single-mode with non-zero shifted dispersion (ITU-T G.655)*
- *M – multimode with core and sheath diameter ratio 50 : 125 mm (ITU-T G.651)*
- *B – multimode with core and sheath diameter ratio 62.5 : 125 mm (IEC 60793-2)*

[d] 1 … 6 – number of optical modules in cable
[e] quantity of optical fibers in the module:
- *1 … 16*

(f) quantity of insulated copper conductors in cable
Optical modules are completed with string fillers up to total number of core elements

Manufacturing of cables with two copper insulated remote power conductors instead of two string fillers is possible
Manufacturing of cables in climate version F is possible
Manufacturing of cables with steel strength element is possible
It is possible to manufacture cables with gel-filled core or dry core (with water-blocking yarns and tapes)
It is possible to manufacture cables with a number of core elements up to and including 18

Order placing: sample of indication (corresponds to configuration pattern)
ОБгПо-36А6(6х6)-3.5 • ТУ У 31.3-00214534-050:2005

Cables are used for:
- *installation in pipes (including air installation method), blocks, collectors at risk of damage by rodents*

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan

7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

500401-035060004072

ОБгПо * 6 – 3.5
ТУ У 31.3-00214534-050:2005

Fiber optic module-core cables, corrugated steel-tape armoured, with polyethylene outer sheath

TECHNICAL SPECIFICATIONS

Number of cable core elements	units	6
Number of optical fibers in cable	units	4 ... 96
Electrical resistance of sheath insulation, not less than	MOhm • km	2000
Permissible tensile force	kN	3.5
Permissible crushing force, no less than	N/10 sm	2000
Operating temperature range	˚C	-40 ... +60
Operating temperature range (in climate version F)	˚C	-60 ... +60
Cable weight (approximate, depending on construction)	kg/km	145 ... 160
Rated outer diameter of the cable (for reference only, depending on construction) **	mm	13 ... 14
Minimum bending radius during laying	mm	280
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 10a: 2160 • 0.4 # 12a: 3220 • 0.6 # 14: **** 4000 • 0.8

Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer

*** The external diameter may differ from the rated up to ± 10 %*

***** Option delivery on not full drum*



CONSTRUCTION

1. Central dielectric strength element
Note: Manufacturing of cables with steel strength element is possible
2. Optic fibers
3. Tube of fiber optic module
4. PET film winding
5. Lapping layer of water-blocking tape or thread
6. Armour of corrugated steel tape, polyethylene-laminated
7. Polyethylene outer sheath

Notes:
- *Optical module twisting is not illustrated.*
- *Manufacturing of cables with two copper insulated remote power conductors instead of two string fillers is possible*
- *It is possible to manufacture cables with gel-filled core or dry core (with water-blocking yarns and tapes)*
- *It is possible to manufacture cables with a number of core elements up to and including 18*

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan